

## **Agro Inox PM - GM**

### **AGRO INOX Enclosure Range with Roller Shutter (PM / GM)**

The AGRO INOX range represents the most advanced protection solution for food-processing environments. Fully manufactured in 304 stainless steel with a micro-bead-blasted finish, it comes in two sizes: the compact **AGRO PM INOX** and the larger, more spacious **AGRO GM INOX**.

Designed to house a complete IT workstation, these enclosures stand out thanks to their **sliding roller shutter with articulated slats** (available in aluminium or stainless steel), equipped with a damper for smooth and safe operation. Ergonomics are maximised through integrated opening handles and shelves with anti-fall edges.



### **Key Strengths**

- **Maximum hygiene and robustness:**  
The 2 mm thick 304 stainless-steel construction ensures exceptional durability and ease of cleaning, meeting the highest industry standards.
- **Protection and sealing:**  
A design engineered to provide long-lasting protection for your equipment in the harshest conditions, with secure closure via lock.
- **Optimised ergonomics:**  
The sliding roller shutter provides full access without any door swing, while the shelves with raised edges prevent documents or equipment from falling.
- **Fully integrated connectivity:**  
Each enclosure is delivered ready for use, with a built-in power supply block and a professional KDL cable entry system.

### **Technical Features**

Both models share a high-quality design with common specifications:

- **Structure:**  
Enclosure body in 2 mm thick 304 stainless steel with micro-bead-blasted finish.
- **Access:**  
Sliding roller shutter with articulated slats (aluminium or stainless steel), equipped with a damper.
- **Security:**  
Lockable closure and internal shelves featuring a 30 mm anti-fall edge.

- **Cable Entry:**

KDL system supplied with blanking plugs and cable pass-through inserts.

## Options or Variants

- Both models in the range share a complete list of **“Food-Industry” options** for advanced customisation:
- Stainless-steel floor stand or wall-mounting bracket.
- Set of 4 castors for floor stand (including 2 with brakes).
- Additional fixed or pull-out shelves (for printer, mouse, etc.).
- Ventilation system (ECA) with IP65 deflector, or heating system (RCA thermostat-controlled heater).
- IP65 sealed inspection window, access hatch, lock, and screen support.
- Cutout-free cable entry system (KDL).